


PATENT APPLICATION COVER SHEET
Attorney Docket No. 0212.68529

I hereby certify that this paper is being deposited with the United States Postal Service as Express Mail in an envelope addressed to: Mail Stop Patent Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on this date.

3/11/04
Date


Express Mail No.: EV032703558US

A PLUNGE-TYPE ROUTER HAVING
IMPROVED PLUNGE RETURN CAPABILITY

Inventors: John B. Freese, Kristopher Baker

GREER, BURNS & CRAIN, LTD.
300 South Wacker Drive
Suite 2500
Chicago, Illinois 60606
Telephone: 312.360.0080
Facsimile: 312.360.9315
CUSTOMER NO. 24978

1 A PLUNGE-TYPE ROUTER HAVING IMPROVED
2 PLUNGE RETURN CAPABILITY

3 BACKGROUND OF THE INVENTION

4 The present invention generally relates to hand held power tools and more
5 particularly to routers.

6 Craftsmen and artisans have been using routers for decades to perform many
7 woodworking tasks, including cutting decorative shapes and edges in wood and other
8 suitable materials. While fixed base routers, i.e., ones where the housing is fixed or
9 locked in a position relative to the base after the depth of cut of the tool bit has been set,
10 are often used by professional artisans, many router users prefer plunge type routers
11 which have a housing that is rapidly movable relative to a base with the amount of
12 vertical movement being determined by a depth limiting mechanism.

13 Plunge routers generally have a housing in which a motor is located, although in
14 certain types of routers a removable motor assembly may be carried by a housing. In this
15 type of situation, generally known in the art as a hybrid router, the motor assembly can be
16 removed from the housing and placed in a fixed base housing so that it can be operated in
17 that manner. If the motor assembly is mounted into a plunge type router housing or if the
18 router is a dedicated plunge-type router, the housing is generally mounted on a base
19 structure of the type that typically has a pair of spaced vertical guide posts along which
20 the housing can be vertically moved. During use, an artisan may press down on the
21 housing, typically by pressing down on handles that extend from opposite sides of the
22 housing or motor assembly so that as the housing is pressed downwardly toward the base
23 structure, the router bit penetrates into a work piece that is to be cut.

24 An adjustable depth of cut mechanism is nearly always provided to control the
25 depth in which the router bit can penetrate the work piece to produce the desired cutting
26 operation. Generally, when the artisan presses down on the handles to have the router bit
27 penetrate the work piece, a handle or lever mechanism can be set to hold the router at the

1 desired position during use. When the router bit is to be removed from the work piece,
2 the lever can be released and springs located in the router around the posts act to push the
3 housing upwardly away from the base structure. Typically, the springs are coil springs
4 that surround each of the posts and bear against the base structure as well as the housing
5 and provide a biasing force tending to separate the two components. It is also typical for
6 the springs to be housed in generally cylindrical or oblong accordion-like baffles that
7 hide the springs from view and to provide a barrier for dust and other debris from coming
8 into contact with the post surface and the interface between the post and openings in the
9 housing in which sliding movement of the housing on the post occurs.

10 Because there are two posts on which the housing must slide, it is not unusual for
11 a particular router design to exhibit a tendency for the housing to bind during sliding
12 movement and one of the solutions to minimize such binding is to have a single spring on
13 one of the posts or to have springs on both posts with the spring force of one of the
14 springs being greater than the other.

15 SUMMARY OF THE INVENTION

16 A preferred embodiment of the present invention is directed to a router having a
17 housing which supports a motor wherein the housing is vertically movable along a pair of
18 spaced vertical guide posts of a base structure and wherein the router includes a flexible
19 baffle which can vertically expand and contract as the housing is moved relative to the
20 base structure and wherein at least one post has a coil spring located within the baffle
21 which is configured to bias the housing away from the base structure, with the coil spring
22 having a generally hourglass shaped configuration. The configuration has outer end
23 portions with larger coil diameters, both of which transition to a center portion with a
24 smaller coil diameter. The hourglass configured coil minimizes the possibility of the coil
25 buckling which could result in a loss of spring force as well as a distortion of the shape of
26 the baffle. Also, the amount of travel that is permitted by the hourglass spring is larger
27 than would be achieved by a comparable uniform coil diameter spring made from the

1 same material, because a number of coils can be telescoped together to produce a smaller
2 compressed or solid height of the spring.

3 DESCRIPTION OF THE DRAWINGS

4 FIGURE 1 is a perspective view of a router in which the preferred embodiment of
5 the present invention may be employed;

6 FIG. 2 is a perspective view of a representative router which utilizes a prior art
7 uniform coil diameter spring surrounding the post of a base structure in which a housing
8 is vertically movable and particularly showing a baffle removed to illustrate the
9 deformation of a uniform coil diameter spring;

10 FIG. 3 is a perspective view of a representative router which utilizes a prior art
11 uniform coil diameter spring surrounding the post of a base structure in which a housing
12 is vertically movable and particularly showing deformation of the shape of a baffle;

13 FIG. 4 is a perspective view of a router particularly illustrating a base structure
14 and housing that is slideable on a pair of posts and which illustrates the hourglass
15 configured spring used in the preferred embodiment;

16 FIG. 5 is a perspective view similar to FIG. 3, but utilizing the hourglass spring of
17 FIG. 6, and particularly showing the absence of deformation of the baffle; and

18 FIG. 6 is a plan view of the hourglass spring that is shown in FIGS. 4 and 5.

19 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

20 A representative router in which the present invention may be implemented is
21 shown generally at 10 in FIG. 1. The router 10 has a removable motor assembly 12 with
22 handles 14, the assembly 12 being installed in a housing 16 that is vertically adjustable
23 relative to a base structure 18 having a pair of posts 20, 22 (see FIG. 2), which are located
24 inside respective baffles 24 and 26. The housing 16 can be moved toward and away from
25 the base structure by sliding along the posts 20 and 22 when manipulated by an operator.
26 In this regard, the operation of the router shown in FIG. 1 is described in detail in patent

1 application entitled "A Hybrid Router", by John B. Freese, Robert H. Bruno and Bjorn J.
2 Gunderson, Serial No. 10/615,726, filed July 9, 2003, which is incorporated by reference
3 herein. As is described in that patent application, a depth of cut adjustment control
4 mechanism is provided to limit the depth of cut of a router bit that is installed in the
5 router and a locking mechanism is also disclosed for holding the bit in position during a
6 routing operation without having to provide a constant downward force on the housing.

7 As is shown in FIG. 2, a uniform coil diameter spring 30 is shown to be installed
8 around the guide post 20 and another uniform coil diameter coil 32 is shown installed
9 around the post 22. As is readily apparent, the diameter of the wire material of the coil
10 30 is larger than the diameter of the material used for the coil 32. This is because it was
11 desired to have a stronger spring force exerted by the spring 30 than spring 32 to
12 overcome a tendency for the housing to bind during a plunge operation. The spring 30 is
13 shown in FIG. 2 to be extensively buckled and the buckling of it produces a deformation
14 of the baffle 24 as shown in FIG. 3. While the spring 32 also appears to be buckled as
15 shown in FIG. 2, it does not exhibit as much force as the spring 30 and does not deform
16 the baffle 26 as shown in FIG. 3.

17 In accordance with a preferred embodiment of the present invention and referring
18 to FIGS. 4-6, a spring 40 having an hourglass configuration is employed and installed
19 around the guide post 20. Because of the hourglass configuration, the baffle 24 shown in
20 FIG. 5 has not been noticeably deformed. The reason is that the center portion of the
21 spring 40 is much smaller than the end portions and the center portion is only slightly
22 larger than the post 20, which prevents the spring from buckling in the manner as is
23 shown for the spring 30 in FIG. 2.

24 With regard to the spring configuration of the preferred embodiment which is
25 shown in its free form in FIG. 6, it preferably has a load characteristic of about 17.5 lbs.
26 at approximately 3-1/2 inches. The spring preferably also has a free length of
27 approximately 7-1/8 inches that is comprised of approximately 15-1/4 coils over its
28 length, with each end being a closed end that is not ground. In other words, the end

1 surfaces of the coils 42 and 44 are generally perpendicular to the axis of the spring so that
2 they are generally flat where they bear upon the upper surface 46 of the base structure 18
3 and the lower surface 48 of the housing 16. The spring 40 is preferably made from 0.065
4 inch diameter high carbon spring steel music wire having ASTM A128 properties. The
5 spring 40 has five portions, a left end portion comprised of four coils 50, a right end
6 portion comprised of four coils 52, a reduced diameter center portion comprised of two
7 coils 54 and two transition portions comprised of two coils 56 and two coils 58 which
8 gradually change from the smaller diameter size coils 54 to the larger diameter end
9 portions 50 and 52. The inside diameter of the end portions 50 and 52 may be different
10 from one another but are preferably approximately equal for the preferred embodiment
11 shown in FIG. 6 and are approximately 0.750 inch. The outside diameter of the small
12 center portion coils 54 is preferably 0.560 inch.

13 An important consideration in the design of the spring is to provide the necessary
14 spring force but still have the necessary travel. While the spring force can be increased
15 by increasing the diameter of the wire that is used to make the spring, the increased
16 thickness results in a taller solid or compressed height, which reduces the amount of
17 travel that can be accomplished during a plunge operation. In the present design, the
18 diameter of the center portion coils 54 and the transition coils 52 are small enough so that
19 they can collapse into the larger coils 50 and 52 as well as portions of the transition coils
20 56 and 58. In this manner, the solid height of the compressed spring will be less than
21 would otherwise exist were the coils of uniform diameter. In the preferred embodiment
22 configuration of the spring 40, the approximately 15-1/4 coils will have a solid height
23 that is equivalent to approximately ten uniform coils having the larger diameter end
24 portions 50, for example. Thus, the hourglass configuration not only prevents spring
25 buckling with its attendant reduction in applied force or at least inconsistent applied force
26 is not only minimized, but the solid height of the hourglass configuration is less than that
27 which would exist were the spring to have a uniform coil diameter.

28 With regard to the spring 32, it is preferably made of a smaller diameter music

1 wire, namely, approximately 0.29 inch and is preferably made of the same material as the
2 spring 40. It preferably has a free length of approximately 9 inches. A coil outside
3 diameter of approximately 0.843 inch and has a closed end not ground end configuration.

4 For a totally flat end surface for springs, particularly those which have a larger
5 wire diameter, it is common to grind the end surfaces so that a greater degree of flatness
6 can be achieved at the very end of the wire portion which forms the end coil.

7 While various embodiments of the present invention have been shown and
8 described, it should be understood that other modifications, substitutions and alternatives
9 are apparent to one of ordinary skill in the art. Such modifications, substitutions and
10 alternatives can be made without departing from the spirit and scope of the invention,
11 which should be determined from the appended claims.

12 Various features of the invention are set forth in the following claims.